


73284.000 White
 LED 6W 600lm 3000K warm white
 Switchable
 Version 3
 Connected load 8W
 Spherolit lens, oval flood

Product description

Housing and bracket: cast aluminium, powder-coated. 0°-90° tilt. Bracket on transadapter rotatable through 360°. Internal wiring.
 ERCO Transadapter for 3-circuit track: plastic. Electronic control gear. Circuit pre-selection.
 LED module: high-power LEDs on metal-core PCB. SDCM<2. CRI>90. L80/B10 50000h. Collimating lens made of optical polymer. Lens rotatable through 360°.
 Weight 0.37kg
 Energy efficiency class EEL A+
 LMF E



LED 6W 600lm 3000K warm white

h(m)	E(lx)	D(m)	
		C0	C90
		62°	17°
1	1387	1.20	0.30
2	347	2.40	0.60
3	154	3.61	0.90
4	87	4.81	1.20
5	55	6.01	1.49



Mounting
 ERCO 3-circuit track
 Hi-trac 3-circuit track

Planning data

Cleaning (a)	1				2				3			
	P	C	N	D	P	C	N	D	P	C	N	D
LMF	0.96	0.94	0.90	0.86	0.93	0.91	0.86	0.81	0.92	0.90	0.84	0.79
RSMF	0.96	0.92	0.87	0.81	0.96	0.92	0.87	0.81	0.96	0.92	0.87	0.81

Hours of operation (h)	1000	2000	4000	6000	8000	10000	20000	30000	40000	50000
LLMF	0.99	0.99	0.98	0.97	0.96	0.95	0.92	0.88	0.84	0.81
LSF	1	1	1	1	1	1	1	1	1	1

- MF LMFxRSMFxLLMFxLSF
- MF Maintenance Factor
- LMF Luminaire Maintenance Factor
- RSMF Room Surface Maintenance Factor
- LLMF Lamp Lumens Maintenance Factor
- LSF Lamp Survival Factor
- P Room pure
- C Room clean
- N Room normal
- D Room dirty